

Product	Form Factor			Maximum Load (Total)	Maximum Load (Per Outlet)	Outlet Type	Total Outlets	Amount Of Receptacles (Always on)	Amount Of Receptacles (Switched)	Front Panel Courtesy Outlet	Amount Of Receptacles (Sequenced)	Sequenced Banks	Delay Time (Seconds)	Remote On	Sequencing / Control	Advanced Series Mode® Surge Elimination	Impedance Tolerant® EMI / RFI Filtering	COUVS® - Catastrophic Under / Over Voltage Shutdown	SurgeX/CE® - Inrush Current Elimination	Fixed 240cm Mains Cord	Self Test Circuit With Visual Indicator	Task Lamp Connectors (XLR)
	Rack	Stand Alone	Hard Wired																			
SEQ1216i	1U			16A	10A	IEC	10	2			8	4	2 / 5 / 10 / 15 / 20	✓	✓	✓	✓	✓		✓	✓	
SX1216i	1U			16A	10A	IEC	11	2	8	✓						✓	✓			✓	✓	
SX1216RTi	1U			16A	10A	IEC	11	2	8	✓				✓		✓	✓	✓	✓	✓	✓	
SX1216RLi	1U			16A	10A	IEC	10	2	8							✓	✓	✓	✓	✓	✓	2
SX2216	2U			16A	16A	CEE7/7	7	1	5	✓						✓	✓			✓	✓	
SX2216RT	2U			16A	16A	CEE7/7	7	1	5	✓				✓		✓	✓	✓	✓	✓	✓	
SX2216RL	2U			16A	16A	CEE7/7	6	1	5							✓	✓	✓	✓	✓	✓	2
SA162		✓		16A	16A	CEE7/7	2	2								✓	✓			✓	✓	
SXN1230			✓	20A												✓	✓				✓	